

## Jenolite Rust Shield Technical Data Sheet

### Product Features

Jenolite Rust Shield is a specially formulated protective barrier. It can be used to protect tools and hardware from moisture and rust. It can also be used in other automotive applications. It applies a permanent acrylic protective coating that is not easily removed.

### Directions for storage and use

- Consult the safety data sheet prior to use.
- Shake can well before use.
- Clean target surface, ensure it is clear of dirt, oil and contaminants.
- Mask off any areas that are not to be sprayed.
- For best results test spray a flat surface (cardboard box or similar) to become familiar with the spray before using for the chosen application.
- Spray on to the target surface in smooth strokes from 15-30cm away.
- Spray in light coats, building up if required, leaving 15-30 minutes between coats.
- Leave to dry for 24 hours before using.
- This Aerosol should be stored out of direct sunlight and below 50°C.
- Guaranteed for use up to 1 year after manufacture.
- We recommend testing an inconspicuous area before use, to ensure the desired effect is achieved.
- For best results use between 10°C and 25°C. Extremes of temperature affect drying performance.

### Pack Sizes

400ml (65x157mm)

Boxes of 12

### Physical Properties

- Appearance: Clear.
- Base Type: Acrylic polymer in solvent.
- Propellant: Propane/Butane mix.
- Flammability: Extremely flammable. Flash point -60°C.
- Creates a clear acrylic coating that may change the appearance of some surfaces.

### Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.